


# EMB-762

## Industrial Embedded Board Computer



### Features

- ◆ Ultra Low Voltage Intel® Celeron® M Processor upto 1GHz CPU
- ◆ Low ESR, high frequency Cap. Retention
- ◆ Intel 82852GM/82801DB system chipset
- ◆ 4 COM, 4 USB 2.0 ports
- ◆ Turly Fanless solution



### Technical Specifications

| SYSTEM                    |   |
|---------------------------|---|
| CPU                       | Intel Mobile Celeron M 600MHz low power embedded CPU                        |
| Chipset                   | Intel 82852GM NB, ICH4 SB   |
| Memory                    | 1 x DDR-SDRAM 184 pin socket, up to 1GB                                     |
| BIOS                      | 4M firmware HUB Award license BIOS  |
| Ethernet Connector        | Intel 82551 support 10/100 Base-T   |
| Audio                     | AC97 codec  |
| Watchdog Timer            | 255 levels timer internal, setup by software                                |
| PCI                       | 1 x PCI slot for expansion  |
| Power management          | I/O peripheral devices support power saving and doze/standby/suspend modes. |
| Power Connector           | 20 pin ATX power connector  |
| Touch Controller (Option) | Touch Controller Onboard Chip   |
| Temperature               | Operating: 0°C ~ 55°C<br>Storage: -10°C ~ 70°C                              |
| Humidity                  | 5% ~ 95% RH, non-condensing   |
| Dimensions                | 219mm x 159mm   |
| RoHS                      | RoHS Compliant  |

| Display           |  |
|-------------------|--|
| VGA connector     | 1 x DB-15 VGA connector supporting up to 1600 x 1200<br>1 x internal VGA pin head                                  |
| LCD connector     | Dual channel LVDS 18 bits / LVDS 24 bits (optional)  |
| IO                |  |
| IDE               | 1 x 40 pin IDE port<br>1 x 44 pin IDE port   |
| Serial Port       | 4 x COM ports (Support One COM port RS-232/422/485)  |
| USB               | 2 x USB 2.0 ports<br>2 x internal USB2.0 ports   |
| Audio             | 1 x Line-out<br>1 x Line-in<br>1 x Mic-in  |
| Parallel Port     | 1 x multi-mode parallel port (SPP/EPP/ECP)   |
| Keyboard/Mouse    | 2 x 6-pin mini-DIM PS/2 keyboard and mouse connector   |
| IrDA              | 1 x internal IrDA  |
| Order Information |  |
| EMB 762-A1        | Single board, Socket 479 w/ Intel82852GM(w/CPU Cooler); support LCD, LAN, expansion 1 PCI slot; ATX power          |
| EMB 762-B1        | Single board, Pentium M, ULV Celeron M 600(w/Fanless Heat sink); support LCD, LAN, expansion 1 PCI slot; ATX power |